

DUALCOM S

by CYBER SWITCHING®



Remote Management

The Dualcom S is an elegant solution for control and monitoring no matter the location. Stay in touch with IT equipment conveniently 24 hours a day, 7 days a week.

Dualcom S gives you power to do it better.

The Dualcom S not only allows remote power management, but also represents a new approach to managing your system. Save energy by scheduling shutdown periods. Monitor current consumption to utilize valuable rack space efficiently.

Dualcom S means power control and monitoring from wherever you are.

The Dualcom S enables scheduled or manual on/off control of each outlet and monitoring of the load on each outlet. Two interfaces provide convenient access to your system— TCP/IP and Serial Port.

Features:

- Individual outlet current metering and control
- Cyber Breaker® the Virtual Circuit Breaker available on all models
- Events tracked in an event log, including change of outlet states, logins and logoffs, and user IP addresses.
- Receive event logs via SNMP, Syslog, and e-mail automatically
- Total system current displayed on seven-segment LED display
- Outlet memory restores outlet states in event of power outage
- Supports temperature and humidity sensor for environmental monitoring



Dualcom S Series Technical Specifications

Model	Part Number	Input Voltage	Current Per Input Cord**	Input Connection	Current Per Outlet Receptacle**	Outlet Type	Dimensions
Dualcom S 440i	2000020	120-240	40 A (2 x 20 A)	(2) IEC 60320 C20	20	(4) IEC 60320 C19	17W x 10.35D x 1.75H
Dualcom S 460L5	2000021	120	60 A (2 x 30 A)	(2) NEMA L5-30P	30	(4) NEMA L5-30R	17W x 10.35D x 3.50H
Dualcom S 460L6	2000013	208-240	60 A (2 x 30 A)	(2) NEMA L6-30P	30	(4) NEMA L6-30R	17W x 10.35D x 3.50H
Dualcom S 816i-EU	2000033	200-240	16 A	(1) IEC 60320 C20	10	(8) IEC 60320 C13	17W x 10.35D x 1.75H
Dualcom S 820	2000011	120	20 A	(1) IEC 60320 C20	20	(8) NEMA 5-20R	17W x 10.35D x 1.75H
Dualcom S 830i	2000010	120-240	30 A (2 x 15 A)	(2) IEC 60320 C20	15	(8) IEC 60320 C13	17W x 10.35D x 1.75H
Dualcom S 832i-EU	2000034	200-240	32 A (2 x 16 A)	(2) IEC 60320 C20	10	(8) IEC 60320 C13	17W x 10.35D x 1.75H
Dualcom S 840	2000012	120	40 A (2 x 20 A)	(2) IEC 60320 C20	20	(8) NEMA 5-20R	17W x 10.35D x 1.75H
Dualcom S 840i	2000022	120-240	40 A (2 x 20 A)	(2) IEC 60320 C20	20	(8) IEC 60320 C19	17W x 10.35D x 1.75H
Dualcom S 1620V	2000014	120	20 A	(1) NEMA 5-20P	20	(16) NEMA 5-20R	1.75W x 2.75D x 65.00H
Dualcom S 1620VATX	2000035	120	20 A	(2) NEMA 5-20P	20	(16) NEMA 5-20R	1.75W x 2.75D x 65.00H
Dualcom S 1630ViCB	2000036	120	30 A	(1) NEMA L5-30P	15	(16) IEC 60320 C13	1.75W x 2.75D x 65.00H
Dualcom S 1630ViCB	2000005	208-240	30 A	(1) NEMA L6-30P	15	(16) IEC 60320 C13	1.75W x 2.75D x 65.00H
Dualcom S 1630ViCBMO	2000037	120	30 A	(1) NEMA L5-30P	C13=15 + C19=20	(10) IEC 60320 C13 + (6) IEC 60320 C19	1.75W x 2.75D x 65.00H
Dualcom S 1630ViCBMO	2000006	208-240	30 A	(1) NEMA L6-30P	C13=15 + C19=20	(10) IEC 60320 C13 + (6) IEC 60320 C19	1.75W x 2.75D x 65.00H
Dualcom S 1630ViCBMOMV	2000007	120-240	30 A	(1) NEMA L14-30P	C13=15 + C19=20	(10) IEC 60320 C13 + (6) IEC 60320 C19	1.75W x 2.75D x 65.00H
Dualcom S 1632ViCB	2000018	200-240	32 A	(1) IEC 60309 32A 2P+E	15	(16) IEC 60320 C13	1.75W x 2.75D x 65.00H
Dualcom S 1632ViCB-EU	2000038	200-240	32 A	(1) IEC 60309 32A 2P+E	10	(16) IEC 60320 C13	1.75W x 2.75D x 65.00H
Dualcom S 1632ViCBMO	2000019	200-240	32 A	(1) IEC 60309 32A 2P+E	C13=15 + C19=20	(10) IEC 60320 C13 + (6) IEC 60320 C19	1.75W x 2.75D x 65.00H
Dualcom S 1632ViCBMO-EU	2000039	200-240	32 A	(1) IEC 60309 32A 2P+E	C13=10 + C19=16	(10) IEC 60320 C13 + (6) IEC 60320 C19	1.75W x 2.75D x 65.00H
Dualcom S 1640V	2000004	120	40 A (2 x 20 A)	(2) NEMA 5-20P	20	(16) NEMA 5-20R	1.75W x 2.75D x 65.00H

i- Indicates International Unit

L - Indicates Locking Plug and/ or Receptacle

V - Indicates Vertical Format

CB - Indicates Circuit Breaker

* Various Input Cord Cap Options Available

** Safety Agency Derating in U.S. For Continuous Current Is 80% Of Rating Shown

All Models Can Be Customized For Different Configurations.

Input Cords Sold Separately. Various Lengths Available