



Maximize Uptime...

Reduce Overhead

The Elegant Solution for control and monitoring from wherever you are.

Stay in touch with your IT equipment conveniently 24 hours a day, 7 days a week.



The **DUALCOM™** offers a TCP/IP interface allowing you to connect through a web browser, a menu driven telnet session or using SNMP commands.

IOIOI

The **DUALCOM™** offers a serial interface allowing out-of-band connectivity to control, monitor and protect your outlets.

Features:

- Monitor current on each outlet
- Turn each outlet on/off
- Schedule outlets on/off
- Web browser, telnet and SNMP management
- Serial enabled
- Manage users
- Login/password security
- Event logging
- Customize outlet names
- Over/under current warnings
- Intuitive user interface

The **DUALCOM™** allows remote power management and represents a new approach to managing your system. Save energy by scheduling shutdown periods. Properly allocate current requirements.

The **DUALCOM™** will maximize your uptime and reduce your overhead.



Can be customized for different configurations

CYBER@SWITCHING®

DUALCOM 1630ViCB PLUS C13R L630P 2 QTY 20 AMP (0 RU)

Part # 1013024

The Dualcom PLUS allows remote power management and represents a new approach to managing your system. Save energy by scheduling shutdown periods. Monitor current consumption to utilize valuable rack space efficiently.

Technical Specifications

Output	
Output Voltage	208-240 VAC
Output Connections	(16) IEC 60320 C13
Output Current per Bank	20 A
Output Current per Receptacle	15 A
Input	
Input Voltage	208-240 VAC
Input Frequency	50/60 Hz
Input Connection Type	NEMA L6-30P
Cord Length	12 feet
Circuit Breaker	(2) 20 A UL Listed
Input Current	30 A
Load Capacity	7200 VA
Physical	
Net Weight	10.10 lbs.
Maximum Height	65.00 inches
Maximum Width	1.75 inches
Maximum Depth	2.75 inches
Shipping Weight	13.10 lbs.
Shipping Height	72.00 inches
Shipping Width	7.50 inches
Shipping Depth	4.50 inches
Color	Black
Environmental	
Operating Environment	0 to 45° C
Maximum Operating Relative Humidity	95%
Storage	-25 to 85° C
Regulatory Approval (Pending)	cUL Listed, UL Listed, IEC 60950-1, FCC Class A
Warranty	
Standard	2 years repair or replace
Extended	Optional
Communication	
Network Settings	10BaseT
Serial Settings	RS-232 (Cisco DCE pin-out)

Outlet/Receptacle:

Input/Plug:

Features:

- Events tracked in an event log, including change of outlet states, logins and logoffs, and user IP addresses.
- Receive event logs via SNMP, syslog, and e-mail automatically
- Assign descriptive names to each outlet
- Total system current displayed on seven-segment LED display
- Outlet memory restores outlet states in event of power outage
- Outlet states, under- and over-current warnings, and Virtual Circuit Breaker™ notices provided on front panel

DERATE TO 80% FOR CONTINUOUS LOAD
SUBJECT TO CHANGE WITHOUT NOTICE

Rev 2.1



Distributed by:

i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com